

# CHILL&FLOW™ SERIES

MODEL	COMPRESSORS		ESTIMATED COOLING CAPACITY						PUMPS	
	TOTAL HP	QTY/HP	25°F (-4°C) Leaving Fluid 90°F (32°C) Ambient		30°F (-1°C) Leaving Fluid 90°F (32°C) Ambient		35°F (1.6°C) Leaving Fluid 90°F (32°C) Ambient		CIRCULATION	PROCESS
			BTU/HR	kW	BTU/HR	kW	BTU/HR	kW	QUANT/HP	QUANT/HP
PE1008B1R405-A-VA	3/4 HP	1 EA / .75HP	5500	1.6	6090	1.8	6600	1.9	1 EA 1/6 HP	1 EA 1/6 HP
PE1008B1R405-A-VB	3/4 HP	1EA / .75 HP	5500	1.6	6090	1.8	6600	1.9	1 EA 1/6 HP	1 EA 1/6 HP

TOTAL HP	MATERIAL		TANK	GLYCOL FIELD CONNECTION	DIMENSION (inches)			ESTIMATED WEIGHT		ELECTRICAL		
										Minimum Circuit Ampacity		Max Overcurrent Protection
										POWER	(MCA)	(MOP)
3/4 HP	FRAME	HOUSING	SIZE	SIZE	LENGTH	WIDTH	HEIGHT	SHIPPING	OPERATING			
3/4 HP	GALVANIZED SHEET METAL	GALVANIZED SHEET METAL	5 Gal	1 in	33	30	27	400 LBS	450 LBS	120/1/60	25 AMPS	30 AMPS
3/4 HP	GALVANIZED SHEET METAL	GALVANIZED SHEET METAL	5 Gal	1 in	33	30	27	400 LBS	450 LBS	230/1/60	15 AMPS	15 AMPS



## PRO REFRIGERATION, INC.

326 8TH ST SW  
AUBURN, WA 98001

319 FARMINGTON RD  
MOCKSVILLE, NC 27028

WWW.PROCHILLER.COM  
PARTS - PROCHILLERPARTS.COM  
TECH SUPPORT - MYCHILLER.COM  
INFO@PROREFRIGERATION.COM

800.845.7781

