



DESIGN DATA

DESCRIPTION	UNITS	VARIABLE
WORKING PRESSURE	Mpa	NORMAL PRESSURES
DESIGN PRESSURE	Mpa	NORMAL PRESSURES
WORKING TEMP	°F (°C)	23 (-5)~122 (50)°
DESIGN TEMP	°F (°C)	14 (-10)~122 (50)°
MATERIAL	GRADE	304 SS
FULL VOLUME	GAL (L)	144 (547)
EFFECTIVE VOLUME	GAL (L)	120 (454)

CONNECTION TABLE

NO.	NAME	CONNECTION SIZE	CONNECTION TYPE
A	DRAIN	2"	TRI-CLAMP
B	SENSOR PORT	2.5"	TRI-CLAMP
C	CIP (SPRAY DISK)	1.5"	TRI-CLAMP
D	CIP CONNECTION	1.5"	TRI-CLAMP
E	VENT	4"	TRI-CLAMP

Customer:

Submittal No.:

SUBMITTAL

Model:

DPV1603662

Drawn By:

BJH

Date:

7/2/2020

Rev.

Date

Description

2

3/30/21

ADD SPRAY DISK, RQW

Notes:

SOLD BY:

PRO Refrigeration, Inc.

326 8th Street SW Auburn, WA 98001

T: (253) 735-9466 / F: (253) 735-2631

www.prochiller.com

DAIRYPro Vat