



### Main

Product or component type	Industrial Control Transformer
Power Rating	50 VA
Primary Voltage	208/230/460 V
Secondary Voltage	115 V
Type	TF

### Complementary

Number of Phases	1 phase
Power Rating	50 VA
Primary to Secondary Voltage	208/230/460 V 115 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Maximum Height	4.81 in (122.17 mm)
Maximum Width	3.38 in (85.85 mm)
Maximum Depth	3.34 in (84.84 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC1

### Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	221 °F (105 °C)

### Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901039273
Nbr. of units in pkg.	1
Package weight(Lbs)	4.35 lb(US) (1.97 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	5.40 in (13.716 cm)
Package 1 width	6.40 in (16.256 cm)
Package 1 Length	7.30 in (18.542 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------